



Positioner Type SPC, for stroke actuators

Model:

- For pneumatic linear actuators in single-acting function
- SPC*: with large air capacity for DIASTAR DN>50
- Operation/configuration via DIP switch internal
- Supply voltage 24V DC
- Control signal 4-20 mA
- Contactless (wear-free) analog inductive position sensor
- Electrical connection multi-pin plug (not included)
- Protection class IP65/IP67
- Binary input (fail-safe position, changeover)
- Operating status (automatic / manual)
- Analog feedback (0/4...20 mA, 0...5/10 V) for setpoints and actual values
- Approved and listed according to cULus

Option:

- Adaption for mounting on pneumatic actuator
- Multipole plug

Type	Code	Weight (kg)	Y4 (mm)	Lmax (mm)	Wmax (mm)
SPC	199 190 620	0.460	117.5	104.5	99.5
SPC*	199 190 621	0.460	117.5	104.5	99.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>