



Positioner Type RPC, for rotary actuators

Model:

- For pneumatic rotary actuators in single-acting and double-acting function
- Operation/configuration via DIP switch internal
- Supply voltage 24V DC
- Control signal 4-20 mA
- Conductive plastic rotary potentiometer as displacement transducer
- Electrical connection multi-pin plug (not included)
- Protection class IP65/IP67
- Binary input (fail-safe position, changeover)
- Operating status (automatic / manual)
- Analog feedback (0/4...20 mA, 0...5/10 V) for setpoints and actual values
- Approved and listed according to cCSAus

Option:

- Adaption for mounting on pneumatic actuator
- Multipole plug

Type	Code	Weight	Y4	W1	W2	L1	L2
		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
RPC	199 190 640	1.000	83.5	48	62	60.5	100.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>